



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX PTB 07.0012U** issue No.:1

Certificate history:
Issue No. 1 (2012-1-27)
Issue No. 0 (2007-3-9)

Status: **Current**

Date of Issue: **2012-01-27** Page 1 of 4

Applicant: **R. STAHL Schaltgeräte GmbH**
Am Bahnhof 30
74638 Waldenburg (Württ.)
Germany

Electrical Apparatus: **Indicating light for panel mounting types 8013/3.2-.. and 8013/3.4-..**
Optional accessory:

Type of Protection: **Flameproof enclosures "d", Increased safety "e", Encapsulation "m", Intrinsic safety "i"**

Marking: Ex dem IIC and Ex dm ia IIC

*Approved for issue on behalf of the IECEx
Certification Body:* Dr.-Ing. Ulrich Johannsmeyer

Position: Department Head "Intrinsic Safety and Safety of Systems"

*Signature:
(for printed version)*

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Physikalisch-Technische Bundesanstalt (PTB)
Bundesallee 100
38116 Braunschweig
Germany





IECEx Certificate of Conformity

Certificate No.: IECEx PTB 07.0012U

Date of Issue: **2012-01-27**

Issue No.: **1**

Page 2 of 4

Manufacturer: **R. STAHL Schaltgeräte GmbH**
Am Bahnhof 30
74638 Waldenburg (Württ.)
Germany

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2004 Edition: 4.0	Electrical apparatus for explosive gas atmospheres - Part 0: General requirements
IEC 60079-1 : 2001 Edition: 4	Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
IEC 60079-11 : 1999 Edition: 4	Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'
IEC 60079-18 : 1992 Edition: 1	Electrical apparatus for explosive gas atmospheres - Part 18: Encapsulation 'm'
IEC 60079-7 : 2006-07 Edition: 4	Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:
DE/PTB/ExTR07.0016/00

Quality Assessment Report:
DE/BVS/QAR10.0002/02



IECEx Certificate of Conformity

Certificate No.: IECEx PTB 07.0012U

Date of Issue: 2012-01-27

Issue No.: 1

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The indicating light for panel mounting, type 8013/3.2-... and type 8013/3.4-... is intended for installation in the walls and covers of enclosures for electrical equipment or for control boards or control cabinets. The indicating light of type Intrinsic Safety "i" is operated as an intrinsically safe unit when connected to intrinsically safe circuits.

Nomenclature

Indicating light for panel mounting	Type	8013/abc-de-f
a	3 = Design	
b	Variation 1 = standard 2 = intrinsic safety	
c	Type of connection 2 = Cage clamp 4 = Plug	
d, e, f	numerals or letters without influence to explosion-protection	

Electrical data

Rated insulation voltage	550 V
Type	8013/31.
Rated voltage	10.8 V - 270 V AC/DC
Type	8013/32.
Rated voltage	10.8 V - 28 V AC/DC
	Suited for connection to intrinsically safe circuits (Signalling circuit) with the following maximum values: $U_i = 28 \text{ V}$ $I_i = 150 \text{ mA}$ $P_i = 1 \text{ W}$ L_i and C_i are negligibly low
Frequency range	0 to 60 Hz
Rated cross section	with cage clamp 0.5 mm ² – 2.5 mm ²
	with clamp-type terminal 0.5 mm ² – 1.5 mm ² connection with terminal sockets with notch for plug connector width 2.8-08 in accordance with DIN 46247 or IEC 61210

Special conditions for safe use

- The indicating light for panel mounting, type 8013/31., shall be installed in such a way that its rear end is protected against mechanical damage.
- The indicating light for panel mounting, type 8013/312 and 8013/314, are suited for installation in enclosures used in connection with inflammable gases. For inflammable gases, the enclosures shall meet the requirements of an approved type of protection as specified in IEC 60079-0.
- The indicating light for panel mounting, type 8013/32., may be operated as an intrinsically safe unit when connected to intrinsically safe circuits of category "ia" or "ib".
- Since type of protection IP20 is provided at the terminals of the indicating light for panel mounting, type 8013/322 (intrinsically safe), installation in an enclosure of type of protection Increased Safety is not necessary.
- The terminals of the indicating light for panel mounting, type 8013/324 (intrinsically safe), shall be protected by a protective enclosure designed to type of protection IP20.
- The signalling circuit is electrically isolated from earth.
- The maximum permissible ambient temperature range is -30 °C to +60 °C.

8. The maximum ambient temperature has to be adjusted as required for the bezel used for the indicating light.
Routine testing for pressure resistance can be dispensed with for the luminous element (flameproof enclosure) of the indicating light for panel mounting.

CONDITIONS OF CERTIFICATION: NO



IECEx Certificate of Conformity

Certificate No.: IECEx PTB 07.0012U

Date of Issue: **2012-01-27**

Issue No.: **1**

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

New QAR