





- > High ingress protection IP66/67 is standard, IP68 can be delivered upon request
- > Drainage flange in box prevents penetration of water
- > Manufactured in acid proof stainless steel (AISI 316L)
- > Tailor made size and performance is possible
- > Stainless steel type label spot welded to the cover
- > Several earthing alternatives
- > Maximum strength and corrosion resistance
- > Low lifetime maintenance cost











**E6** 



The TEF10582095 is an electric thermostat with ambient (local) temperature sensing.

Typical applications included:

Process heating control, frost protection.

	ATEX					
Zone	0	1	2	20	21	22
For use in		х	х			

Explosion Protection	
Marking	
Europe (ATEX)	
Certificates	
Europe (ATEX)	NEMKO 01ATEX097

WebCode T1058B

# **Ambient Sensing Electronic Thermostat**

Series TEF 1058



#### **Selection Table**

Version	Measuring range	Order number
TEF 1058 Ambient Sensing Electronic Thermostat	0 100 °C	TEF10582095


### **Technical Data**

Electrical data			
Rated operating voltage	250 V AC		
Switching capacity	16 A / 250 V AC		
Contact arrangement	1 NO contact		
Mechanical data			
Enclosure material	AISI 316L / EN1.4404, electro polished		
Degree of protection	IP66 / IP67		
Weight	4.5 kg		
Equipped with	2 pc. M25 Stopping plugs in box 1 pc. M25 Cable gland Type: E204/3B/M25 1 pc. M25 Drain plug 3 pc. Earth terminals PHOENIX USLKG6N 5 pc. Terminals PHOENIX UK5N 3 pc. Terminals PHOENIX UK3N		
	2 pc. Terminals PHOENIX UK3N blue 1 pc. Label kit		

## **Accessories and Spare Parts**

Designation	Description	Order number
Connection kit	for Thermon cables KSX and HTSX, gasket 5 x 11	TEF9177224
	for Thermon cables BSX and VSX, gasket 5 x 13	TEF9177203
	for Thermon cables TSX and RSX, gasket 5 x 15	TEF9177204
Flexible conduit	SS316; inner diam. 18.8.mm, outer diam. 22.3 mm; length: 2 m	TEF7000080
	SS316; inner diam. 18.8.mm, outer diam. 22.3 mm; length: 25 m	TEF7000081
Adapter	for flexible conduit	TEF50791115
Cable gland for power cable	E204 / 3B / M25 - 9 mm; Ø 13 17.1 mm; with lock nut	TEF9147118
	E204 / 3A / M25 - 9 mm; Ø 14.1 20.1 mm; with lock nut	TEF9147119

# Dimensional Drawings (All Dimensions in mm) - Subject to Alterations



We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.