



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:	IECEx BAS 05.0087X	Page 1 of 5	<u>Certificate history:</u>
Status:	Current	Issue No: 8	Issue 7 (2012-01-31)
Date of Issue:	2018-04-17		Issue 6 (2010-10-19)
Applicant:	R. Stahl Schalgerate GmbH Am Bahnhof 30 Waldenburg 74638 Germany		Issue 5 (2010-04-14)
Equipment:	A Yodalex Type YL60C Audible/Visual Alarm		Issue 4 (2008-11-14)
Optional accessory:			Issue 3 (2008-08-20)
Type of Protection:	Flameproof and Dust		Issue 2 (2008-03-31)
Marking:	Ex db IIB + H2 T4 Ta -20°C to + 60°C Gb		Issue 1 (2008-01-04)
	Ex tb IIIC T135°C Ta -20°C to + 60°C Db IP66		Issue 0 (2006-03-17)
	or when provided with a 5J xenon where applicable		
	Ex db IIB + H2 T6 Ta -20°C to + 40°C Gb		
	Ex tb IIIC T85°C Ta -20 °C to + 40°C Db IP66		

Approved for issue on behalf of the IECEx
Certification Body:

R S Sinclair

Position:

Technical Manager

Signature:
(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

SGS Baseefa Limited
Rockhead Business Park
Staden Lane
Buxton, Derbyshire, SK17 9RZ
United Kingdom





IECEX Certificate of Conformity

Certificate No.: **IECEX BAS 05.0087X**

Page 2 of 5

Date of issue: 2018-04-17

Issue No: 8

Manufacturer: **R. Stahl Schalgerate GmbH**
Am Bahnhof 30
Waldenburg
74638
Germany

Additional
manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2011 Explosive atmospheres - Part 0: General requirements
Edition:6.0

IEC 60079-1:2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
Edition:7.0

IEC 60079-31:2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Edition:2

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

Quality Assessment Report:

[DE/BVS/QAR10.0002/16](#)

IECEX ATR:

GB/BAS/ExTR11.0080/00
GB/BAS/07.0187/00
GB/BAS/ExTR08.0115/00, 08.0036/00

File reference:

11/0217
07/1033
GB/BAS/ExTR08.0197/00 and 0121/00



IECEx Certificate of Conformity

Certificate No.: **IECEx BAS 05.0087X**

Page 3 of 5

Date of issue: 2018-04-17

Issue No: 8

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

YODALEX TYPE YL60C SOUNDER/STROBE is an audible/visual alarm device comprising a cast aluminium body and end covers each secured by four M5, 30mm long socket head cap screws Grade A4-80.

One end cover accommodates a well glass assembly and the other a sounder assembly.

The well glass assembly comprises an untoughened glass part cemented into the end cover with a silicone material and retained with a threaded steel clamping ring. A coloured polycarbonate lens is clipped into position over the wellglass. In addition a wire guard is permanently secured to the body of the wellglass assembly by four tamperproof fixing screws.

The sounder assembly comprises a breathing device (sinter) located in a centrally machined bore provided in the end cover by an interference fit and is retained internally by a circlip. Cemented in position externally to this arrangement is a moulded trumpet to which is fixed, by screws, a horn cover.

A nitrile rubber 'O' ring is provided within a machined groove at each face of the body to which each end cover is secured. A printed circuit board arrangement incorporating terminal facilities is located between guide channels integrally cast with the inside wall of the body and held in position by the sounder unit. Soldered to the top edge of the board is a xenon lamp rated at 5J which is positioned centrally within the well glass.

Internal and external earth facilities are provided.

The equipment provides a degree of ingress protection of IP66.

The equipment is intended to be so mounted that it operates with the horn cover orientated upwards.

Cable entries are provided by two threaded apertures.

Due to the lens, horn cover and trumpet materials presenting a possible electrostatic risk, and therefore to obviate the risk of creating an ignition source, a warning label is fixed externally to the enclosure indicating that these should be cleaned only with a damp cloth.

The YODALEX TYPE YL60C SOUNDER/STROBE may also be identified as:-

- i) YODALEX TYPE YL60C AUDIBLE/VISUAL ALARM or
- ii) YODALEX TYPE YL6.

The equipment is available in the following ratings:-

- i) 24Vd.c., 570mA
- ii) 115Va.c., 200mA
- iii) 230Va.c., 100mA

The designation code is made up as follows: YL60C*50*EU

where the first * indicates the voltage rating (D= 24Vd.c.; L=115Va.c.; N=230Va.c.) and the second * indicates the lens colour.

VARIATION 0.1

Omission of the well glass assembly and replacement by a plain flat end cover. The printed circuit board is replaced by a version designed to control the sounder only and which incorporates terminal facilities.

In this form the equipment is designated YODALEX TYPE YA60C SOUNDER.

The equipment is intended to be so mounted that it operates with the horn cover orientated upwards.

The equipment is available in the following ratings:-

- i) 24Vd.c., 350mA
- ii) 115Va.c., 110mA
- iii) 230Va.c., 55mA

The designation code is made up as follows: YA60C*EU



IECEx Certificate of Conformity

Certificate No.: **IECEx BAS 05.0087X**

Page 4 of 5

Date of issue: 2018-04-17

Issue No: 8

where * indicates the voltage rating (D= 24Vd.c.; L=115Va.c.; N=230Va.c.)

The YODALEX TYPE YA60C SOUNDER may also be identified as:-

- i) YODALEX TYPE YA60C AUDIBLE ALARM
- ii) YODALEX TYPE YO6.

VARIATION 0.2

Omission of the sounder assembly and replacement by a plain flat end cover. The printed circuit board is replaced by a version designed to control the xenon lamp only and which incorporates terminal facilities.

In this form the equipment is designated YODALEX TYPE FL60C STROBE.

The equipment is intended to be so mounted that it operates with the well glass cover orientated downwards.

The equipment is available in the following ratings:-

- i) 24Vd.c., 220mA
- ii) 115Va.c., 90mA
- iii) 230Va.c., 45mA

The designation code is made up as follows: FL60C*50*EU

where the first * indicates the voltage rating (D= 24Vd.c.; L=115Va.c.; N=230Va.c.) and the second * indicates the lens colour.

The YODALEX TYPE FL60C STROBE may also be identified as:

- i) YODALEX TYPE FL60C VISUAL ALARM or
- ii) YODALEX TYPE V6.

Variation 0.3

Alternative cement material for the wellglass assembly.

SPECIFIC CONDITIONS OF USE: YES as shown below:

1. The equipment incorporated flameproof joints which have a maximum gap less than that stated in the standard IEC 60079-1. The user must ensure that the diametric clearance associated with the spigot joint at each end cover does not exceed 0.064mm and that the gap between the face of each end cover and the body does not exceed 0.038mm.
2. For replacement purposes the end cover fixing screws shall be of minimum grade A4-80 stainless steel.
3. The cable entry device shall be suitably sealed to maintain the IP66 rating



IECEx Certificate of Conformity

Certificate No.: **IECEx BAS 05.0087X**

Page 5 of 5

Date of issue: 2018-04-17

Issue No: 8

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above) **Variation 8.1**

To allow the product YL60C Audible/Visual Alarm, to be assessed against the following standards: IEC 60079-1:2014 Edition 7 and IEC 60079-31:2013 Edition 2

ExTR: GB/BAS/ExTR18.0036/00	File Reference: 17/0704
------------------------------------	--------------------------------