

IS530.M1 Smart Phone Set mining ROW 订货号 307071



- Explosion-protected phone for mining industry with push-to-talk option
- SOS key for lone-worker protection
- NFC access control
- universal
- powerful replaceable battery for multi-shift operation
- Android Enterprise Recommended
- zero touch capable
- managed via MDM system

<STEPREF A="AT_TitleWeb-shop" O="PV 2276217"



Thanks to its freely programmable key, optionally with PTT, the professional mobile phone can be used like a radio device. Its ISM interface for the connection of other accessories such as RSM or PTT headsets make it suitable for MCPTT communication. The Android Enterprise Recommended device is zero touch capable and can be easily managed via an MDM system. The powerful battery and the charging options via desktop or multi-charger complete the highlights of this ultra-robust mobile device with a comfortable feel.

技术数据

防爆

应用范围	矿用 M1、M2
使用范围 (防火湿保护)	M1 M2
适用范围	采矿业: 欧盟 (CE / ATEX) 全球 (IECEX) 南非 (SANS) 澳大利亚和新西兰 (ANZEx)
IECEX 认证	EPS 19.0062X
ATEX 认证	EPS 19 ATEX 1 126 X
SANS 认证	MTEEx 0901/20.0013
ANZEx 认证	ANZEx 20.2002X
IECEX 防火湿保护	Ex ia I Ma IP64
ATEX 防火湿保护	I M1 Ex ia I Ma IP64
SANS 防火湿保护	Ex ia I Ma IP64
ANZEx 防火湿保护	Ex ia I Ma

电气数据

处理器型号	Qualcomm SDM660 Octa-core
内存	4 GB
数据存储器	64 GB 内存 + 高达 128 GB 的 SD 卡
操作系统	Android 10 (upgr. 13)
移动标准	2G , 3G , 4G
介质接口	WLAN 802.11 a/b/g/n/ac/e/k/r/h
附加接口 1	蓝牙 5
附加接口 2	13MP-AF-摄像头 (后置)
附件 3/选项框	5MP 前置摄像头
SD 卡型号/容量	microSD/最大 128 GB

IS530.M1 Smart Phone Set mining ROW 订货号 307071

电气数据

SIM卡号	双 SIM 卡
SIM 卡尺寸	micro

显示屏

显示屏尺寸, 英寸	4.50
显示屏尺寸 cm	11.43
显示屏分辨率	FWVGA
触摸屏	电容式
触摸屏材料	大猩猩玻璃, 康宁第三代
背光照明灯	LED 技术

环境条件

环境温度	-20 – 60
环境温度	-20 °C ... +60 °C

机械数据

防护等级 (IP)	IP68
MIL 标准	810G (h/l 温度, 冲击, 振动)
宽度	80 mm
高度	155 mm
深度	25 mm
重量	325 g
重量	0.72 lb

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。