

IS-SW1.1 Smartwatch 订货号 312329



- Ideal for Mobile Worker applications
- intuitive voice control for hands-free working
- monitoring vital signs
- NFC timekeeping and access control
- SOS key for emergencies

<STEPREF A="AT_TitleWeb-shop" O="PV 2483632"



The world's first explosion-protected industrial smartwatch for ATEX/IECEX zones 1/21 can be used in a highly flexible way for employee safety and organisation in the company. Coupled via Bluetooth with the suitable smartphones, it functions as a supplementary hand-free wrist display for important messages, alarms and measured values. Use the IS-SW1.1 to monitor vital signs, make an emergency call with GPS location and to emulate RFID smart cards for convenient access control.

技术数据
防爆

使用范围 (区)	1 2 21 22
使用范围 (区)	1 2 21 22
应用范围	1 区, 21 区 2 区, 22 区
适用范围	欧盟 (CE / ATEX) 全球 (IECEX) 英国 (UKEX)
IECEX 认证	EPS 22.0028X
ATEX 认证	EPS 22 ATEX 1 196 X
UKCA 认证	EPS 22 UKEX 1 196 X
IECEX 气体防爆	Ex ib IIC T4 Gb
IECEX 粉尘防爆	Ex ib IIIC T135°C Db
ATEX 气体防爆	Ex II 2G Ex ib IIC T4 Gb
ATEX 粉尘防爆	Ex II 2D Ex ib IIIC T135°C Db
UKCA 气体防爆	II 2G Ex ib IIC T4 Gb
UKCA 粉尘防爆	II 2D Ex ib IIIC T135°C Db
电气数据	
内存	1 GB
数据存储	8 GB
可选数据接口 1	蓝牙 5.1
附件 3/选项框	BT5.1, NFC, Wifi 2.4 GHz

IS-SW1.1 Smartwatch 订货号 312329

显示屏	
显示屏尺寸, 英寸	1.60
显示屏尺寸 cm	4.06
显示屏分辨率	320x360 像素
触摸屏	电容式
环境条件	
环境温度	-20 – 55
机械数据	
防护等级 (IP)	IP68
MIL 标准	810H
宽度	45 mm
高度	54 mm
深度	17.6 mm
重量	70 g
重量	0.15 lb

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。