

IS930.1 Tablet Set ROW no camera 订货号 317083



- Ideal for Mobile Worker concepts
- without camera
- Android Enterprise Recommended
- zero touch capable
- certified for Zone 1, 2, 21, 22
- user-friendly and easy to handle with hand strap
- individually programmable buttons
- display can be operated with gloved fingers

<STEPREF A="AT_TitleWeb-shop" O="PV 2692022"



The robust and powerful tablet is the ideal partner for our MOBILE WORKER concepts in hazardous and harsh ambient conditions. The IoT generation tablet is Android Enterprise Recommended. Its zero touch capability makes it quick to use and ideal for maintenance applications in an IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap and a separate leather bag with a shoulder/belt or carry strap system are further highlights.

技术数据

防爆

使用范围 (区)	1 2 21 22
使用范围 (Division)	Class I, Division 1 Class II, Division 1 Class III
应用范围	1 区 , 21 区 2 区 , 22 区
适用范围	欧盟 (CE / ATEX) 全球 (IECEX) 美国 (NEC) 加拿大 (CEC) 中国 (PCEC) 巴西 (INMETRO) 韩国 (KCS) 日本 (JNIOSH) 南非 (SANS)
IECEX 认证	EPS 19.0034X
ATEX 认证	EPS 19 ATEX 1 071 X
NEC 认证	70220243
CEC 认证	70220243
INMETRO 认证	BRA 20.GE0004X
KCS 认证	20-KA4BO-0127X 20-KA4BO-0128X
PCEC 认证	CE20.2367X
JNIOSH 认证	CSAUK 20JPN031X CSAUK 20JPN032X
SANS 认证	MTEEx 0901/20.0012

IS930.1 Tablet Set ROW no camera 订货号 317083

防爆	
IECEX 气体防爆	Ex ib IIC T4 Gb
IECEX 粉尘防爆	Ex ib IIIC T135°C Db IP6X
ATEX 气体防爆	Ex II 2G Ex ib IIC T4 Gb
ATEX 粉尘防爆	Ex II 2D Ex ib IIIC T135°C Db IP6X
NEC 气体防爆	Class I, Div 1, Groups A, B, C, D, T4
NEC 粉尘防爆	Class II, Div 1, Groups E, F, G, T135°C Class III, Div 1
CEC 气体防爆	Class I, Div 1, Groups A, B, C, D, T4
CEC 粉尘防爆	Class II, Div 1, Groups E, F, G, T135°C Class III, Div 1
INMETRO 气体防爆	Ex ib IIC T4 Gb
INMETRO 粉尘防爆	Ex ib IIIC T135°C Db IP6X
KCS 防爆	Ex ib IIC T4 Ex ib IIIC T135°C
PCEC 气体防爆	Ex ib IIC T4 Gb
PCEC 粉尘防爆	Ex ibD 21 T135°C
JNIOOSH 气体防爆	Ex ib IIC T4 Gb
JNIOOSH 粉尘防爆	Ex ib IIIC T135°C Db IP6X
SANS 气体防爆	Ex ib IIC T4 Gb
SANS 粉尘防爆	Ex ib IIIC T135°C Db IP6X
电气数据	
处理器型号	Qualcomm SDM660 Octa-core
内存	4 GB
数据存储器	64 GB 内存 + 高达 128 GB 的 SD 卡
操作系统	Android 10 (upgr. 13)
移动标准	2G, 3G, 4G
介质接口	WLAN 802.11 a/b/g/n/ac/e/k/r/h
可选数据接口 1	蓝牙 5
SD 卡型号/容量	microSD/最大 128 GB
SIM 卡数量	单 SIM 卡
SIM 卡尺寸	micro
显示屏	
显示屏尺寸, 英寸	8.00
显示屏尺寸 cm	20.32
显示屏分辨率	全高清 1200 x 1920 像素
触摸屏	电容式
触摸屏材料	大猩猩玻璃, 康宁第三代
背光照明灯	LED 技术
环境条件	
环境温度	-20 – 60
机械数据	
防护等级 (IP)	IP68
MIL 标准	810G (h/l 温度, 冲击, 振动)
宽度	156 mm
高度	237 mm

IS930.1 Tablet Set ROW no camera 订货号 317083

机械数据

深度	22 mm
重量	890 g
重量	1.96 lb

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。