



## WebCode SEALB

Selection Table				
Product Description	CMP sealing disc			
WebCode	SEALB			
Material	Nickel-plated brass			
Gauge	0.5 mm			
Product Type	Use	Diameter	Art. No.	Weight
ID105	0A** 40E**/C**/PX**/T3CDS/TE1FU	–	253064	26 g
ID125	50sE**/C**/PX**/T3CDS/TE1FU	–	253066	30 g
ID155	63A**	–	253069	34 g
ID175	75sA**	–	253071	38 g
ID185	63E**/C**/PX**/T3CDS/TE1FU	–	253072	39 g
Product Description	CMP sealing disc For cable entry			
WebCode	SEALB			
Material	Nickel-plated brass			
Gauge	0.5 mm			
Product Type	Use	Diameter	Art. No.	Weight
ID01	A** - 20s A** - 20s16 SS2K / PXSS2K - 20s SS2K / PXSS2K - 20s16	17.3 mm	253055	5 g
ID02	E** / C** / PX** - 20s E** / C** / PX** - 20s16 SS2K / PXSS2K - 20 T3CDS / TE1FU - 20s T3CDS / TE1FU - 20s16	20.1 mm	253056	6 g
ID03	A** - 20	21.4 mm	253057	7 g
ID04	E** / C** / PX** - 20 SS2K / PXSS2K - 25 T3CDS / TE1FU - 20	26.6 mm	253058	10 g
ID05	A** - 25	29.4 mm	253059	12 g
ID06	E** / C** / PX** - 25 E** / C** / PX** - 25s SS2K / PXSS2K - 32 T3CDS / TE1FU - 25 T3CDS / TE1FU - 25s	32.4 mm	253060	15 g
ID07	A** - 32	35.5 mm	253061	20 g
ID08	A** - 40 E** / C** / PX** - 32 SS2K / PXSS2K - 40 T3CDS / TE1FU - 32	40.8 mm	253062	22 g
ID09	A** - 50s SS2K / PXSS2K - 50s	47 mm	253063	25 g
ID11	A** - 50 SS2K / PXSS2K - 50	53.4 mm	253065	28 g

**Selection Table**

Product Description	CMP sealing disc For cable entry			
WebCode	SEALB			
Material	Nickel-plated brass			
Gauge	0,5 mm			
Product Type	Use	Diameter	Art. No.	Weight
ID13	A** - 63s SS2K / PXSS2K - 63s	60.4 mm	253067	32 g
ID14	E** / C** / PX** - 50 SS2K / PXSS2K - 63 T3CDS / TE1FU - 50	64 mm	253068	33 g
ID16	E** / C** / PX** - 63s SS2K / PXSS2K - 75s T3CDS / TE1FU - 63s	69.5 mm	253070	36 g
ID19	SS2K / PXSS2K - 75 A** - 75	77.5 mm	253073	40 g