



- Flexible configuration due to pushbutton, mushroom pushbutton, mushroom stay-put button, mushroom stay-put button with key lock, key-operated button, key-operated switch
- Easy assembly thanks to single-hole mounting (D 30)
- Codable "latching", "spring return", "key not removable" functions
- Plug-in connection with 6 m connection line

MY R. STAHL 8003D



R. STAHL Series 8003 control buttons and/or switches for panel mounting switch load, control and signal circuits up to 6 A. Depending on the type, they are complete or incomplete explosion-protected equipment with corresponding requirements for installation. As an option, various actuators are available.



	IECEx / ATEX						
	Zone	0	1	2	20	21	22
Installation in		•	•		•	•	

	NEC® 500 CE Code Appendix J						
	Division	Class I		Class II		Class III	
Installation in		•		•			

	CE Code Section 18						
	Zone	NEC® 505 Class I			NEC® 506		
Installation in		•	•				

Selection Table						
Actuator		Key-operated switch actuator With key actuator MS1				
Number of switching positions		2				
Figure	Number of NCs	Number of NOs	Contact material	Product Type	Art. No.	Weight
	1	1	Silver-nickel	8003/113-008-2-r-MS1-6 UL	218604	125 g
	2	–	Silver-nickel	8003/123-008-2-r-MS1-6 UL	218605	125 g
Actuator		Key-operated switch actuator With key actuator MS1				
Number of switching positions		3				
Figure	Number of NCs	Number of NOs	Contact material	Product Type	Art. No.	Weight
	–	2	Silver-nickel	8003/133-008-3-rr-MS1-6 UL	213542	125 g
Actuator		Mushroom stay-put button EM-STOP				
Figure	Number of NCs	Number of NOs	Contact material	Product Type	Art. No.	Weight
	1	1	Silver-nickel	8003/113-010S-6 UL	217964	730 g
	2	–	Silver-nickel	8003/123-010S-6 UL	217965	125 g
Actuator		Pushbutton				
Figure	Number of NCs	Number of NOs	Contact material	Product Type	Art. No.	Weight
	1	1	Silver-nickel	8003/113-001-6 UL	213516	125 g
	–	2	Silver-nickel	8003/133-001-6 UL	213540	125 g

Selection Table

Actuator		Rotary actuator, small Not padlockable				
Number of switching positions		2				
Figure	Number of NCs	Number of NOs	Contact material	Product Type	Art. No.	Weight
	1	1	Silver-nickel	8003/113-726-2-r-6 UL	213524	125 g
Actuator		Rotary actuator, small Not padlockable				
Number of switching positions		3				
Figure	Number of NCs	Number of NOs	Contact material	Product Type	Art. No.	Weight
	1	1	Silver-nickel	8003/143-726-3-tt-6 UL	213556	727 g
	–	2	Silver-nickel	8003/133-726-3-tt-6 UL	213546	125 g

- yellow label for EM-STOP function is enclosed
- plates must be ordered separately; see accessories
- key-operated switch with "spring-return" and/or "key not removable" on request
- versions with other locking cylinders on request
- key switches type 8003/1...008-. and control switches type 8003/1...-726-3 are codable ("latching", "spring-return", "key removable")

Technical Data

Variant	8003/1.3-...	8003/1.3-...S
Explosion Protection		
IECEX gas explosion protection	Ex db eb IIC T6 Gb	Ex db eb IIC T6 Gb
IECEX dust explosion protection	Ex tb IIIC T80 °C Db	Ex tb IIIC T80 °C Db
ATEX gas explosion protection	Ⓜ II 2 G Ex db eb IIC T6 Gb	Ⓜ II 2 G Ex db eb IIC T6 Gb
ATEX dust explosion protection	Ⓜ II 2 D Ex tb IIIC T80 °C Db	Ⓜ II 2 D Ex tb IIIC T80 °C Db
Certificates	ATEX (PTB), Canada (UL), IECEx (PTB), Korea (KGS), USA (UL)	ATEX (PTB), Canada (UL), IECEx (PTB), Korea (KGS), USA (UL)
Declaration of Conformity	ATEX (EUK), ATEX (Simple apparatus), China (CCC), Declaration of Conformity (ATEX)	ATEX (EUK), ATEX (Simple apparatus), China (CCC), Declaration of Conformity (ATEX)
Notes	Product label may vary. Series devices have certification according to ATEX, IECEx, NEC® and CE Code.	
Electrical Data		
Rated operational voltage AC	500 V	500 V
Rated operational current	6 A	6 A
Switching capacity AC-12	500 V / 6 A / max. 3000 VA	500 V / 6 A / max. 3000 VA
Switching capacity AC-15	400 V / 6 A / max. 1250 VA	400 V / 6 A / max. 1250 VA
Switching capacity DC-13	110 V / 1 A / max. 110 W	110 V / 1 A / max. 110 W
Switching capacity DC-13<SoftReturn/>2 contact elements in series	60 V/6 A	60 V/6 A
Ambient Conditions		
Ambient temperature	-20 °C ... +60 °C	-55 °C ... +60 °C
Ambient temperature	-4 °F ... +140 °F	-67 °F ... +140 °F
Ambient temperature NEC®	-30 °C ... +60 °C	-55 °C ... +60 °C
Ambient temperature NEC®	-22 °F ... +140 °F	-67 °F ... +140 °F
Mechanical Data		
Degree of protection (IP) (IEC 60529)	Reverse side IP65, front side IP66	Reverse side IP65, front side IP66
Silicone-free	Yes	No
Conductor length	6 m	6 m
Conductor length, inches	236.22 in	236.22 in
Type of connection cable	ÖLFLEX 4x1 mm²	ÖLFLEX 4x1 mm²
Connection cross-section	0.75 ... 1.5 mm²	0.75 ... 1.5 mm²
Connection cross-section AWG	20 AWG ... 14 AWG	20 AWG ... 14 AWG

Control Buttons / Switches for Panel Mounting


Series 8003 Plug-in Connection with Connection Line and Connection Chamber
for ATEX / IECEx and NEC® / CE Code Applications

STAHL


E4

Technical Data		
Variant	8003/1.3-...	8003/1.3-...S
Mechanical Data		
Depth of cut-out	130 mm	130 mm
Mounting depth, inches	5.12 in	5.12 in
Service life, min.	10 ⁸ operating cycles	10 ⁸ operating cycles
Mounting / Installation		
Tightening torque	3 Nm	3 Nm
Tightening torque lbf in	26.55 lbf in	26.55 lbf in
Components		
Entry 1	8161/7-M16-0902	8161/7-M16-0902
Entry 1 type	Polyamide cable gland, black	Polyamide cable gland, black


Technical Drawings – Subject to Alterations



Schematic 8003/113
NO / NC positive opening
Numbers in brackets according to core identification



Schematic 8003/123
NC positive opening
Numbers in brackets according to core identification



Schematic 8003/133
NO
Numbers in brackets according to core identification



Schaltbild 8003/143
NC positive opening / NO
Numbers in brackets according to core identification











Accessories			
Figure	Description	Art. No.	Weight
Actuator			
	Control switch, not padlockable 2 positions: 0 = latching I = latching	155533	28 g
	Control switch, not padlockable 2 positions: 0 = spring return I = spring return	155542	28 g
	Control switch, not padlockable 3 positions: I = free codable 0 = latching II = free codable (all necessary coding elements are included)	155534	28 g
	Pushbutton	155525	23 g
	Key-operated switches with 2 switching positions, MS1	155528	49 g
	Mushroom stay-put button EM-STOP	261756	100 g
Locking devices			
	8602A0753 H24 for not actuated pushbutton / selector switch BG001, BG005	155372	81 g
	8602A0754 for actuated pushbutton / selector switch BG001, BG005	155402	28 g
	8602A0755 for not actuated pushbutton / selector switch BG001, BG005	155431	34 g
Protective collar			
	8602A0751 metal for pushbutton / selector switch / mushroom stay-put button with key lock / mushroom stay-put button / mushroom pushbutton Ø 39 BG001, BG003, BG005, BG008, BG009, BG010, BG012	155326	77 g
Spare key			
	Closing MS1	107109	8 g












Control Buttons / Switches for Panel Mounting

Series 8003 Plug-in Connection with Connection Line and Connection Chamber
for ATEX / IECEx and NEC® / CE Code Applications

STAHL

E4

Spare Parts			
Figure	Description	Art. No.	Weight
Label mount			
	Label mount, size 1, without symbol label Text: 1 line for actuators to fit Ø 30.5 mm holes	155632	1 g
	Label mount, size 2, without symbol label Text: 1 or 2 lines for actuators to fit Ø 30.5 mm holes	155687	2 g
	Label mount, size 3, without symbol label Text: 1, 2 or 3 lines for actuators to fit Ø 30.5 mm holes	155844	2 g
Symbol label for pushbutton and selector switch			
	Colour: blue Please specify text or symbol	155910	1 g
	Colour: green Please specify text or symbol	155900	1 g
	Colour: white Text: START	155889	1 g
	Colour: blue Text: RESET	155894	1 g
	Colour: black Text: Ab	155886	1 g
Label, yellow, general			
	for Ø 39 actuator (EM-STOP)	223571	1 g
Symbol label for pushbutton and selector switch			
	Colour: black Text: Auf	155883	1 g

Spare Parts			
Figure	Description	Art. No.	Weight
Symbol label for pushbutton and selector switch			
	Colour: black Symbol: Arrow	155749	1 g
		155761	1 g
	Colour: red Symbol: Arrow	155567	1 g
	Colour: black Text: Links	155827	1 g
	Colour: black Text: Rechts	155837	1 g
	Colour: black Text: Open	155868	1 g
	Colour: black Text: CLOSE	155878	1 g
	Colour: black Text: Zu	155874	1 g
	Colour: red Text: OFF	155654	1 g
	Colour: green Text: ON	155671	1 g
Insert discs for label holder			
	1-line Plain Material: PVC Colour: White Self-adhesive	238271	10 g











Control Buttons / Switches for Panel Mounting

Series 8003 Plug-in Connection with Connection Line and Connection Chamber
for ATEX / IECEx and NEC® / CE Code Applications

STAHL

E4

Spare Parts			
Figure	Description	Art. No.	Weight
Symbol label for pushbutton and selector switch			
	Colour: red Text: AUS	155634	1 g
Insert discs for label holder			
	2-line Plain Material: PVC Colour: White Self-adhesive	238272	10 g
Symbol label for pushbutton and selector switch			
	Colour: black Text: AUS	155806	1 g
Insert discs for label holder			
	3-line Plain Material: PVC Colour: White Self-adhesive	238273	10 g
Symbol label for pushbutton and selector switch			
	Colour: black Text: EIN	155862	1 g
	Colour: red Text: STOP	155615	1 g
	Colour: black Text: STOP	155795	1 g
	Colour: black Text: I	155846	1 g
	Colour: green Text: I	155689	1 g
	Colour: white Text: I	155892	1 g
	Colour: black Text: II	155854	1 g

Spare Parts			
Figure	Description	Art. No.	Weight
Symbol label for pushbutton and selector switch			
	Colour: green Text: II	155706	1 g
	Colour: red Text: O	155596	1 g
	Colour: black Text: O	155783	1 g
	Colour: black Text: I O	155771	1 g
	Colour: blue Blank label without text	155911	1 g
	Colour: yellow Blank label without text	155914	1 g
	Colour: red Blank label without text	155897	1 g
	Colour: green Blank label without text	155901	1 g
	Colour: white Blank label without text	155908	1 g
	Colour: black Blank label without text	155905	1 g
Coding kit for key-operated switch			
	Coding element, 1 x red, 1 x yellow	155403	1 g
	Coding element, 1 x green, 1 x red	155432	1 g
	Coding element, 2 x yellow	155373	1 g

Control Buttons / Switches for Panel Mounting

Series 8003 Plug-in Connection with Connection Line and Connection Chamber for ATEX / IECEx and NEC® / CE Code Applications



E4

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations

