

8166/11-06-NE Art. No. 139087



- Hazardous location conduit hubs "increased safety"
- Wide range of NPT thread sizes
- Large temperature range of use
- Globally marked, IECEx, ATEX and cULus
- Integrated self-loosening protection through threaded pin

MY R. STAHL 8166A



R. STAHL's 8166 series conduit hubs are used to insert permanently installed conduit systems with NPT threads into electrical equipment with type of protection Increased Safety "e" or Protection by Enclosure "tb" and suitable for NEMA type 4X installation.

### Technical Data

#### Explosion Protection

Scope of validity	USA Canada European Union (ATEX) IECEX
Application range (zones)	1 2 21 22
IECEX gas certificate	IECEX PTB 06.0095 U
IECEX gas explosion protection	Ex eb IIC Gb
IECEX dust certificate	IECEX PTB 06.0095 U
IECEX dust explosion protection	Ex tb IIIC Db
ATEX gas certificate	PTB 00 ATEX 1114 U
ATEX gas explosion protection	⊕ II 2 G Ex eb IIC Gb
ATEX dust certificate	PTB 00 ATEX 1114 U
ATEX dust explosion protection	⊕ II 2 D Ex tb IIIC Db
Certificate ULus	E200949V1S2
Certificate cUL	E200949V1S2
Marking ULus	Class I, Zone 1 AEx e II Class I, Div. 2, Groups A,B,C,D Class II, Div. 2, Groups F,G Class III Type 3, 4, 4X
Marking cUL	Class I, Zone 1 Ex e II Class I, Div. 2, Groups A,B,C,D Class II, Div. 2, Groups F,G Class III Type 3, 4, 4X
Certificates	ATEX (PTB), Canada / USA (UL), Canada (UL), IECEX (PTB)

8166/11-06-NE Art. No. 139087

---

### Electrical Data

PE-pole present	Yes
-----------------	-----

### Ambient Conditions

Ambient temperature	-30 °C ... +100 °C
---------------------	--------------------

Ambient temperature	-22 °F ... +212 °F
---------------------	--------------------

### Mechanical Data

Version	NPT / NPT
---------	-----------

Degree of protection (IP)	IP66
---------------------------	------

Degree of protection (IP) (IEC 60529)	IP66
---------------------------------------	------

Degree of protection (NEMA)	3, 4, 4X
-----------------------------	----------

Material	Zinc
----------	------

Silicone-free	No
---------------	----

Outer diameter	83.57 mm
----------------	----------

Outer diameter in inches	3.298 in
--------------------------	----------

External thread	NPT2
-----------------	------

Thread size	NPT2
-------------	------

Internal thread	NPT2
-----------------	------

Weight	270 g
--------	-------

Weight	0.6 lb
--------	--------

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.