

CMP-781E Art. No. 206294



- Metal Ex e breathers
- Degree of protection: IP66, IP67, IP68
- Operating temperature range: -60 °C ... +130 °C
- Worldwide certification, IECEX, ATEX und cCSAus

MY R. STAHL 781A



In conditions where there are temperature fluctuations and moisture, the metallic Ex e breathers from the 781 series protect electrical wiring from the effects of condensation inside the enclosure. They provide continuous pressure equalisation between the inside of the enclosure and the atmosphere around the enclosure. There are two metric and two NPT thread versions available for this purpose. An integrated connection thread seal and a special fixture nut are included in the standard version. They have worldwide certification according to IECEX, ATEX and cCSAus.

Technical Data

Explosion Protection

Application range (zones)	1 2 21 22
IECEX gas certificate	IECEX CML 18.0187U
IECEX gas explosion protection	Ex eb IIC Gb
IECEX dust certificate	IECEX CML 18.0187U
IECEX dust explosion protection	Ex ta IIIC Da
ATEX gas certificate	CML 18ATEX1327X
ATEX gas explosion protection	Ex II 2 G Ex eb IIC Gb
ATEX dust certificate	CML 18ATEX1327X
ATEX dust explosion protection	Ex II 1 D Ex ta IIIC Da
Notes	The product certification and certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com)

Ambient Conditions

Ambient temperature	-60 °C ... +130 °C
---------------------	--------------------

Mechanical Data

Degree of protection (IP)	IP66
Degree of protection (IP) UL	IP66
Material	Nickel-plated brass
Silicone-free	Yes
Width across corners	33 mm
Thread size	M20
Thread pitch	1,5 mm
Nuts available	With nut

Installation Equipment and Accessories

Breather



CMP-781E Art. No. 206294

Mechanical Data

Packaging unit	1
Weight	80 g
Weight	0.18 lb

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.