Installation Equipment and Accessories

Stopping plug With convex head



CMP-767-D-T1-2 Art. No. 230112



- Ex-d und Ex-e metal stopping plugs
- Large selection of metric thread sizes
- Operating temperature range: -60 °C to +200 °C
- Worldwide certification, IECEx, ATEX, UL and cCSAus

MY R. STAHL 767DA



The metallic Ex-d stopping plugs from the 767 series with a truss head and hexagon socket enable temporary or continuous plugging of unused drilled holes. There is a large selection of different metric thread sizes and types available. They have worldwide certification according to IECEx, ATEX, UL and cCSAus.

Technical Data

Explosion Protection Application range (zones) 1 2 20 21 22 IECEx gas certificate **IECEx CML 18.0177X** IECEx gas explosion protection Fx db IIC Gb IECEx CML 18.0177X IECEX firedamp certificate IECEx firedamp protection Ex db I Mb IECEx firedamp protection 2 Ex eb I Mb CML 18ATEX1320X ATEX gas certificate ATEX gas explosion protection ⟨ II 2 G Ex db IIC Gb ATEX firedamp certificate CML 18ATEX1320X ATEX firedamp protection 🐼 I M2 Ex db I Mb ATEX firedamp protection 2 ⟨€x⟩ I M2 Ex eb I Mb Notes The product certification and certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com) **Ambient Conditions** Ambient temperature -60 °C ... +200 °C **Mechanical Data** Degree of protection (IP) IP66 Degree of protection note IP67 and IP68 mounting in accordance with the specifications of the manufacturer, CMP Material Nylon (polyamide) Silicone-free Yes Drive Hexagon socket Width across corners 26.4 mm Width across flats SW24

R. STAHL Schaltgeräte GmbH | Am Bahnhof 30 | 74638 WALDENBURG Tel. +49 7942 943 1700 | +49 7942 943 1777 | Email: sales.de@r-stahl.com | r-stahl.com Stopping plug With convex head




CMP-767-D-T1-2 Art. No. 230112

Mechanical Data

Outer diameter	26.4 mm	
Thread size	NPT1/2	
Thread length	19.9 mm	
Thread pitch	1,8143	
Packaging unit	1	
Weight	-	

Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations



A = Thread size B = Length L = Thread length D = Outer diameter

SW = Width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.