# **Installation Equipment and Accessories**

# Stopping plug With convex head



### CMP-767-D-T2-2 Art. No. 230113



- Ex-d und Ex-e metal stopping plugs
- Large selection of metric thread sizes
- Operating temperature range: -60 °C to +200 °C
- · Worldwide certification, IECEx, ATEX, UL and cCSAus

### MY R. STAHL 767DA



The metallic Ex-d stopping plugs from the 767 series with a truss head and hexagon socket enable temporary or continuous plugging of unused drilled holes. There is a large selection of different metric thread sizes and types available. They have worldwide certification according to IECEx, ATEX, UL and cCSAus.

#### **Technical Data**

Explosion Protection	
Application range (zones)	1
	2
	20
	21
	22
IECEx gas certificate	IECEx CML 18.0177X
IECEx gas explosion protection	Ex db IIC Gb
CEX firedamp certificate IECEx CML 18.0177X	
IECEx firedamp protection	Ex db I Mb
IECEx firedamp protection 2	Ex eb I Mb
ATEX gas certificate	CML 18ATEX1320X
ATEX gas explosion protection	
ATEX firedamp certificate	CML 18ATEX1320X
ATEX firedamp protection	
ATEX firedamp protection 2	
Notes	The product certification and certificates can be downloaded from the manufacturer's
	homepage
	(www.cmp-products.com)
Ambient Conditions	
Ambient temperature	-60 °C +200 °C
Mechanical Data	
Degree of protection (IP)	IP66
Degree of protection note	IP67 and IP68 mounting in accordance with the specifications of the manufacturer, CMP
Material	Nylon (polyamide)
Silicone-free	Yes
Drive	Hexagon socket
Width across corners	33.6 mm
Width across flats	SW30.5

# **Installation Equipment and Accessories**


# Stopping plug With convex head



## CMP-767-D-T2-2 Art. No. 230113

Mechanical Data		
Outer diameter	33.6 mm	
Thread size	NPT3/4	
Thread length	20.2 mm	
Thread pitch	1,8143	
Packaging unit	1	
Weight	-	

#### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations





A = Thread size

B = Length

L = Thread length

D = Outer diameter

SW = Width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.