Installation equipment and accessories

Stopping plug With convex head



CMP-767-E-T3-2 Art. No. 230114



- Metal Ex d and Ex e stopping plugs
- · Wide selection of metric thread sizes
- Operating temperature range -60 °C to +200 °C
- · Global certification, IECEx, ATEX, cCSAus and UL

MY R. STAHL 767DA



The Series 767 metal Ex d and Ex e stopping plugs with flat round head and hexagon socket make it possible to temporarily or permanently seal unused drilled holes. There is a wide selection of different metric thread sizes available for this. They have global certification according to IECEx, ATEX, UL and cCSAus.

Technical Data

Explosion Protection			
Application range (zones)	1, 2, 20, 21, 22		
IECEx gas certificate	IECEx SIM 15.0002X		
IECEx gas explosion protection	Ex eb IIC Gb		
IECEx dust certificate	IECEx CML 18.0177X		
IECEx dust explosion protection	Ex ta IIIC Da		
IECEX firedamp certificate	IECEx CML 18.0177X		
IECEx firedamp protection	Ex db I Mb		
IECEx firedamp protection 2	Ex eb I Mb		
ATEX gas certificate	CML 18ATEX1320X		
ATEX gas explosion protection			
ATEX dust certificate	CML 18ATEX1320X		
ATEX dust explosion protection			
ATEX firedamp certificate	CML 18ATEX1320X		
ATEX firedamp protection			
ATEX firedamp protection 2			
Notes	The product certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com)		
Ambient Conditions			
Ambient temperature	-60 °C +60 °C		
Mechanical Data	·		
Degree of protection (IP)	IP66		
Degree of protection note	IP67 and IP68 mounting according to the specifications of the manufacturer, CMP		
Material	Nylon (polyamide)		
Silicone-free	Yes		
Drive	Hexagon socket		
Width across corners	41.4 mm		
Width across flats	WAF37.6		

Installation equipment and accessories

Stopping plug With convex head





CMP-767-E-T3-2 Art. No. 230114

MA	chai	nıcal	Data
IAIC	onai	ıııvaı	Data

Hexagon socket width across flats	M10
Height	5.5 mm
Outer diameter	41.4 mm
Thread size	NPT1"
Thread length	25 mm
Thread pitch	2,2087
Packaging unit	1
Weight	-

Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations





A = Thread size

B = Length

L = Thread length

D = Outer diameter

SW = Width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.