Installation Equipment and Accessories

Stopping plug With convex head



CMP-767-D-M7-5 Art. No. 253044



- Ex-d und Ex-e metal stopping plugs
- Large selection of metric thread sizes
- Operating temperature range: -60 °C to +200 °C
- · Worldwide certification, IECEx, ATEX, UL and cCSAus

MY R. STAHL 767DA



The metallic Ex-d stopping plugs from the 767 series with a truss head and hexagon socket enable temporary or continuous plugging of unused drilled holes. There is a large selection of different metric thread sizes and types available. They have worldwide certification according to IECEx, ATEX, UL and cCSAus.

Technical Data

| Explosion Protection | |
|---------------------------------|---|
| Application range (zones) | 1 |
| | 2 |
| | 20 |
| | 21 |
| | 22 |
| IECEx gas certificate | IECEx SIM 15.0002X |
| IECEx gas explosion protection | Ex db IIC Gb |
| IECEx dust certificate | IECEx CML 18.0177X |
| IECEx dust explosion protection | Ex ta IIIC Da |
| IECEX firedamp certificate | IECEx CML 18.0177X |
| IECEx firedamp protection | Ex db I Mb |
| IECEx firedamp protection 2 | Ex eb I Mb |
| ATEX gas certificate | CML 18ATEX1320X |
| ATEX gas explosion protection | |
| ATEX dust certificate | CML 18ATEX1320X |
| ATEX dust explosion protection | |
| ATEX firedamp certificate | CML 18ATEX1320X |
| ATEX firedamp protection | |
| ATEX firedamp protection 2 | |
| Notes | The product certification and certificates can be downloaded from the manufacturer's |
| | homepage |
| | (www.cmp-products.com) |
| Ambient Conditions | |
| Ambient temperature | -60 °C +200 °C |
| Mechanical Data | |
| Degree of protection (IP) | IP66 |
| Degree of protection note | IP67 and IP68 mounting in accordance with the specifications of the manufacturer, CMP |
| Degree of protection (IP) UL | IP66 |
| - | |

Installation Equipment and Accessories


Stopping plug With convex head




CMP-767-D-M7-5 Art. No. 253044

| Mechanical Data | |
|-----------------------------------|---------------------|
| Material | Nickel-plated brass |
| Silicone-free | Yes |
| Drive | Hexagon socket |
| Width across corners | 68 mm |
| Hexagon socket width across flats | M10 |
| Height | 5.5 mm |
| Outer diameter | 68 mm |
| Thread size | M63 |
| Thread length | 15 mm |
| Thread pitch | 1,5 |
| Packaging unit | 1 |
| Weight | 500 g |
| Weight | 1.1 lb |

Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations





- A = Thread size
- B = Length L = Thread length
- D = Outer diameter SW = Width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.