

IS930.2 Tablet Set EEA without camera Art. No. 317084



- Ideal for Mobile Worker concepts
- without camera
- Android Enterprise Recommended
- zero touch capable
- certified for Zone 2, 22
- user-friendly and easy to handle with hand strap
- individually programmable buttons
- display can be operated with gloved fingers

MY R. STAHL MTABLETA

The robust and powerful tablet is the ideal partner for our MOBILE WORKER concepts in hazardous and harsh ambient conditions. The IoT generation tablet is Android Enterprise Recommended. Its zero touch capability makes it quick to use and ideal for maintenance applications in an IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap and a separate leather bag with a shoulder/belt or carry strap system are further highlights.

Technical Data

General	
Version	i.safe Tablet
Explosion Protection	
Application range	Zone 2, Zone 22
Scope	EU (CE / ATEX) Global (IECEX)
IECEX certification	EPS 19.0035X
ATEX certification	EPS 19 ATEX 1 072 X
IECEX gas explosion protection	Ex ic IIC T4 Gc IP64
IECEX dust explosion protection	Ex ic IIIC T135°C Dc IP64
ATEX gas explosion protection	Ⓔ II 3G Ex ic IIC T4 Gc IP64
ATEX dust explosion protection	Ⓔ II 3D Ex ic IIIC T135°C Dc IP64
Electrical Data	
Processor type	Qualcomm SDM660 Octa-core
Main memory	4 GB
Data memory	64 GB int. + SD up to 128 GB
Operating system	Android 10 (upgr. 13)
Mobile standard	2G, 3G, 4G
Interface medium	WiFi 802.11 a/b/g/n/ac/e/k/r/h
Optional interface 1	Bluetooth 5
SD card type/size	MicroSD/up to 128 GB
SIM card number	Single SIM
SIM card size	Micro
Display	
Display size in inches	8.00
Display size in cm	20.32

IS930.2 Tablet Set EEA without camera Art. No. 317084

Display

Display resolution	Full HD 1200 x 1920 pixels
Touch screen	Capacitive
Touchscreen material	Gorilla glass corning 3rd gen.
Backlight	LED technology

Ambient Conditions

Ambient temperature	-20 – 60
---------------------	----------

Mechanical Data

Degree of protection (IP)	IP68
MIL-standard	810G (h/l temp., shock, vibr.)
Width	156 mm
Height	237 mm
Depth	22 mm
Weight	890 g
Weight	1.96 lb

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.