

EC-940-AFZ-HDF-O5I-R1 Art. No. 266894



- Ethernet fibre optics connection
- Ex e connection box for easy installation
- Modern IP camera with ONVIF protocol (Profile S) and Full HD
- Day / night - functionality
- Certified acc. to ATEX and IECEx

WebCode **EC940AFZA**



The R. STAHL's EC-940-AFZ zoom camera has an Ex e connection box, making installation in hazardous areas especially easy. This camera is equipped with a fiber optic connection (Ex op is) and designed for a voltage supply of 24 VDC. It provides clear images even in difficult light - this is ensured by the 32x optical zoom, the WDR image optimisation and the de-fog function, which sharpens contrast in light fog. The camera is integrated into the surveillance system via the ONVIF protocol (Profile S). These robust surveillance camera in an electropolished stainless steel enclosure (316L) is suitable for temperatures ranging from -25 °C to +65 °C and certified acc. to ATEX and IECEx for hazardous areas.

## Technical Data

### Explosion Protection

Application range (zones)	1 2 21 22
IECEx gas certificate	PTB 16.0032X
IECEx gas explosion protection	Ex db eb IIC T4 Gb
IECEx dust certificate	PTB 16.0032X
IECEx dust explosion protection	Ex tb eb IIIC 135 °C Db
ATEX gas certificate	16 ATEX 1019X
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC T4 Gb
ATEX dust certificate	16 ATEX 1019X
ATEX dust explosion protection	Ex II 2 D Ex tb eb IIIC 135 °C Db

### Electrical Data

Rated operational voltage AC	
Rated operational voltage DC	24 V
Rated operational current for DC	1.5 A
Interfaces	FX MM (Ex op is)
Connection	Ethernet port LAN 10/100 T

### Camera Data

Sensor	1/2.8 CMOS
Lens	f = 4.44 (w) to 142.6 mm (t) From F1.6 to F4.4
Viewing angle	62.8° (wide), 2.23° (tele.)
Focus	Automatic focus
Zoom	32x optical

EC-940-AFZ-HDF-O5I-R1 Art. No. 266894

### Camera Data

Resolution	Full HD to 320x180 p
Pixel	Approx. 2.38 megapixels
Accuracy of preset positions	0.02 °
Minimum working distance	1500 mm (wide/tele)
Minimum illumination B/W (ICR-ON)	0.03 lx, F1.6, 1/30s, 50 IRE
Minimum illumination color (ICR-OFF)	0.3 lx F1.6, 1/30S, 50 IRE
Number of streams	Multistream 10 profiles
Frame rate (fps)	H.264 max. 60, MJPEG 15 or 30
S/N ratio	50 dB
Back light compensation	Off / BLC
Electronic shutter	2 to 1/12000s
Compression	H.264, MJPEG
De-fog	Off / Auto / Manual
WDR (dynamic range)	120 dB
White balance	ATW, AWC, manual, internal, External, mercury
Wide Dynamik Range	On/Off

### Software

Network protocol	ONVIF profile S
Network Configuration	TCP/IPv4-IPv6, UDP/IPv4-IPv6, http, NTP, DHCP, QoS, IGMP, Bonjour
Streaming	Unicast / Multicast

### Ambient Conditions

Ambient temperature	-25 °C ... +55 °C
---------------------	-------------------

### Mechanical Data







Version	Movable viewing angle
Degree of protection (IP)	IP66
Enclosure material	Stainless steel 1.4404
Surface treatment	Electropolished
Cable length	0 m
Integrated wiper	No
Feature	Ex-e compartment
Package weight	0 kg
Weight	16 kg
Weight	35.27 lb

### Accessories

Camera multi-cable armoured

Art. No.

EC-940-AFZ-HDF-O5I-R1 Art. No. 266894

	<p><b>VB-CAM-MULTI-Ethernet-ARM</b>  1 x Ethernet cable  3 x power supplies 2.5 mm<sup>2</sup>  7 x data cable 0.34 mm<sup>2</sup>  -60 °C ... +80 °C  19.2 ±0.5 mm outer diameter  IEC 60332-1 flame-resistant  IEC 60754-2 halogen-free  DIN 60811-404 oil-resistant  NEK 606 mud-resistant  Price per metre</p>	252571
<b>Wall mount</b>		
	<p><b>Wall Bracket EC-940-AFZ</b>  Suitable for EC-940-AFZ  Material: 316L stainless steel, electropolished  Weight: ca. 8 kg  Load bearing capacity: max. 40 kg  WxH: 200 x 160 x 330 mm</p>	257043
<b>Pole adapter module</b>		
	<p><b>Pole adapter module EC-940-AFZ</b>  Suitable for EC-940-AFZ  Material: 316L stainless steel, electropolished  Weight: ca. 4.7 kg  Load bearing capacity: max. 40 kg  WxH: 214 x 194 mm  For pole diameter 88 ... 150 mm  May only be used together with wall bracket EC-940-AFZ type 257043</p>	257047
<b>Corner adapter</b>		
	<p><b>Corner adapter EC-940-AFZ</b>  Suitable for EC-940-AFZ series  Material: 316L SST, electropolished  Load bearing capacity: max. 40 kg  WxHxD: 355 x 150 x 211 mm  Weight: ca. 3.2 kg  May only be used together with wall bracket EC-940-AFZ type 257043</p>	257048
<b>Ceiling holder</b>		
	<p><b>Parapet mounting EC-940-AFZ</b>  Suitable for EC-940-AFZ  Material: 316L stainless steel, electropolished  Weight: ca. 4.5 kg  Load bearing capacity: max. 40 kg  WxHxD: 200 x 450.5 x 330 mm</p>	257049
<b>PoE++ Extender</b>		
	<p><b>PoE++ Extender EC-940-HDI-O6H</b>  Cable type: ideally, CAT5e or better  Supports Jumbo Frames up to a max. of 9 kB  Input voltage: 52 ... 57 V DC  Energy consumption: max. 80 W  -20 ... +75 °C  LxBxH: 126 x 95.3 x 30 mm</p>	256800

# Cameras and CCTV Equipment

Zoom camera AFZ camera



EC-940-AFZ-HDF-O5I-R1 Art. No. 266894

---

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.