



- Universally applicable user authentication
- For all HMIs and other applications
- Certified for Zone 2, 22
- MIFARE CLASSIC, DESFIRE, LEGIC MIM, LEGIC ATC, SONY FELICIA, INSIDE SECURE and many other protocols
- Can be operated worldwide in temperatures ranging from -40 °C to +70 °C
- Installation directly in hazardous area
- RS-422, ASCII version

MY R. STAHL RFIDA



The new UB03 is a universally applicable RFID card reader for hazardous areas, certified for Zone 2, 22 acc. to ATEX, IECEx. The reader can be operated as a stand-alone device in hazardous areas or together with a Human-Machine Interface. It works together with all R. STAHL Human Machine Interface (device platforms MANTA, EAGLE, SHARK, RAPTOR).

Technical Data

General	
HMI type	Panel mount device
Card reader type	proximity card reader
Technology	Card reader ASCII
Reader specification	RFID-C6-RS422-01
Chip card technology	MIFARE, LEGIC
Explosion Protection	
Scope	EU (CE / ATEX) International (IECEx)
IECEx gas certificate	IECEx BVS 18.0001
IECEx gas explosion protection	Ex ec nC IIC T4 Gc
IECEx dust certificate	IECEx BVS 18.0001
IECEx dust explosion protection	Ex tc IIIC T115 °C Dc
ATEX gas certificate	BVS 18 ATEX E 002
ATEX gas explosion protection	Ex II 3 G Ex ec nC IIC T4 Gc
ATEX dust certificate	BVS 18 ATEX E 002
ATEX dust explosion protection	Ex II 3 D Ex tc IIIC T115 °C Dc
Certificates and approvals	ATEX IECEx Australia (RCM) China (CCC / CNEx) Kanada (CSA) USA (FM) USA (UL) India (BIS) Korea (KCC)
Electrical Data	
Voltage range DC	4.75 to 30 V DC
Rated operational power	1 W

Operating and Monitoring Systems

Peripherals UB03

RFID chip card reader

UB03-Z2-RFID-C6-RS422-PES-01 Art. No. 272190



Electrical Data

Card reader type	13.56 MHz RFID
Transponder media	LEGIC/MIFARE/DESFire/EV1
Interfaces	RS-422
Protocol reader	ASCII - Variant C6 - Standard
Um max. input voltage	250 V AC

Auxiliary Power

Power supply	5 V DC/24 V DC
Nominal current	0.2 A

Ambient Conditions

Ambient temperature	-40 – 70 °C
---------------------	-------------

Mechanical Data

Version	01
Degree of protection (IP)	IP66
Front enclosure protection type (IP)	IP66
Rear enclosure protection type (IP)	IP66
Enclosure	UB03 & mounting frame
Enclosure material	Aluminium
Wall thickness	1 – 5 mm
Cable length	0 m
Maximum cable length	1000 m
Width	125 mm
Height	185 mm
Depth	55 mm
Depth of cut-out	54.2 mm
Mounting cut-out width	110 mm
Mounting cut-out height	170 mm
Cut-out tolerance	+0.5 mm / -0.3 mm
Front plate	Polyester on aluminium
Installation location	Panel/enclosure
Weight	2.2 lb

Mounting / Installation

Mounting orientation	any
Connection type	Screw terminals
Connection type 1	2.5 mm ² green
Max. USA solid connection terminals	22 AWG

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.