

Control Devices

Contact element For mounting rail mounting NC

With gold-plated contacts

8082/3-11-1-1 Art. No. 275527

STAHL



- Large selection of different actuators
- Versions as an NC with positive opening, NO or disconnect terminal

MY R. STAHL 8082E



R. STAHL Series 8082 contact elements have an NO contact and a positive opening operation NC contact, made from silver-nickel or gold-plated. They can be easily combined with contact blocks and enable customised installations, also due to the large selection of the various actuators. They are connected via screw or spring clamp terminals.

Technical Data

Explosion Protection

Scope of validity	European Union (ATEX) CEC IECEX NEC
Application range (Zones)	1 2
IECEX gas certificate	IECEX PTB 17.0037U
IECEX gas explosion protection	Ex db eb IIC T6 / T5 Gb
IECEX firedamp certificate	IECEX PTB 17.0037U
IECEX firedamp protection	Ex db eb I Mb
ATEX gas certificate	PTB 17 ATEX 1012 U
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC T6 / T5 Gb
ATEX firedamp certificate	PTB 17 ATEX 1012 U
ATEX firedamp protection	Ex I M2 Ex db eb I Mb
UL gas certificate	E182378V1S9
Marking cULus	Class I, Div. 2, Groups A,B,C,D; Class I, Zone 1, AEx/Ex db eb IIC
Certificates	Brazil (ULB), Canada (UL), China (CQST), IECEX (PTB), Korea (KTL), USA (UL)
Notes	Product label may vary. Series devices are labelled with ATEX, IECEX, NEC and CEC.

Electrical Data

Max. rated operational voltage	550 V
Min. rated operational voltage	24 V
Rated operational current	10 mA / 150 A
Rated operational current note	- Gold-plated contacts: 10 to 150 mA switching current - Silver-nickel contacts from 150 mA switching current. - For corrosive environments and offshore applications, we recommend the use of 8082 snap action switches.
Electrical service life	10 ⁹ operating cycles

Control Devices

Contact element For mounting rail mounting NC

With gold-plated contacts

8082/3-11-1-1 Art. No. 275527



Electrical Data

Mechanical service life	10 ⁶ operating cycles
-------------------------	----------------------------------

Ambient Conditions

Ambient temperature °C	-60 °C ... +70 °C (T6) -60 °C ... +85 °C (T5)
Ambient temperature °F	-76 °F ... +158 °F (T6) -76 °F ... +185 °F (T5)
Ambient temperature °F	-60 °C ... +75 °C (T6) -60 °C ... +90 °C (T5)
Ambient temperature °F	-76°F ... +167°F (T6) -76°F ... +194°F (T5)
Operating temperature	-60 °C ... +100 °C
Operating temperature	-76 °F ... +212 °F
Operating temperature NEC	-60 °C ... +95 °C
Operating temperature NEC	-76 °F ... +203 °F

Mechanical Data

Degree of protection (IP) (IEC 60529)	IP20
Enclosure material	Polyamide
Contact material	Gold-plated
Silicone-free	Yes
Solid connection cross section	0.32 – 2.5 mm ²
Connection cross-section AWG single stranded	22 AWG to 14 AWG
Finely stranded connection cross section	0.32 – 2.5 mm ²
Finely stranded connection cross-section AWG	22 AWG to 14 AWG
Connection cross-section, finely stranded with core end sleeve	0.32 – 2.5 mm ²
Connection cross-section, finely stranded with core end sleeve AWG	AWG22 - AWG14
Number of NCs	1
Positive opening operation	Yes
Packaging unit	1
Weight	25 g
Weight	0.055 lbs

Mounting / Installation

Tightening torque	1.2 Nm
Tightening torque lbf in	10.62 lbf in
Connection type	Screw terminal

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations

Accessories

Pushbutton
BG001

Art. No.

Control Devices

Contact element For mounting rail mounting NC

With gold-plated contacts

8082/3-11-1-1 Art. No. 275527

	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: Yes	223691
	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: No	223692
Mushroom pushbutton, black		Art. No.
BG003		
	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: Yes	244563
	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: No	244564
Mushroom pushbutton, red		Art. No.
BG004		
	Ø 39 mm Red/black Designation plate: Red, blank disc without text Silicone-free: Yes	244565
	Ø 39 mm Red/black Designation plate: Red, blank disc without text Silicone-free: No	244566
Mushroom stay-put button with key		Art. No.
BG006		
	Ø 39 mm Red/black Closing: MS1 Silicone-free: Yes	223695
Mushroom stay-put button with key		Art. No.
BG006		
	Ø 39 mm Red/black Closing: MS1 Silicone-free: No	223696
Key-operated switch actuator		Art. No.
BG008		
	Ø 39 mm Black Closing: MS1 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: No	244574


Control Devices

Contact element For mounting rail mounting NC


With gold-plated contacts

8082/3-11-1-1 Art. No. 275527



	<p>Ø 39 mm Black Closing: MS1 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: No</p>	244633
--	---	--------


Mushroom stay-put button with EM-STOP key

BG009	Art. No.	
	<p>Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS1 Silicone-free: Yes</p>	223693
	<p>Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS1 Silicone-free: No</p>	223694


Mushroom stay-put button EM-STOP

BG010	Art. No.	
	<p>Ø 39 mm Yellow/red Designation plate: With yellow backing plate Silicone-free: Yes</p>	223697
	<p>Ø 39 mm Yellow/red Designation plate: With yellow backing plate Silicone-free: No</p>	223698


Mushroom stay-put button, black

BG012	Art. No.	
	<p>Ø 39 mm Black Silicone-free: Yes</p>	223699
	<p>Ø 39 mm Black Silicone-free: No</p>	223700

Mushroom pushbutton 55 mm red

BG014	Art. No.	
	<p>Ø 55 mm Black/red Designation plate: Red, blank disc without text Silicone-free: Yes</p>	244634

Mushroom pushbutton 55 mm red

BG014	Art. No.	
	<p>Ø 55 mm Black/red Designation plate: Red, blank disc without text Silicone-free: No</p>	244635

Control Devices


Contact element For mounting rail mounting NC

With gold-plated contacts


8082/3-11-1-1 Art. No. 275527




Mushroom stay-put button 55 mm EM-STOP

		Art. No.
	Ø 55 mm Yellow/red Designation plate: With yellow backing plate Silicone-free: Yes	244636


Mushroom maintained 55 mm E-STOP

		Art. No.
	Ø 55 mm Yellow/red Designation plate: With yellow backing plate Silicone-free: No	244637


Twin pushbutton

		Art. No.
	Black Silicone-free: Yes	244638
	Black Silicone-free: No	244639

Mushroom pushbutton 55 mm black

		Art. No.
	Ø 55 mm Black Designation plate: Black, blank disc without text Silicone-free: Yes	244642
	Ø 55 mm Black Designation plate: Black, blank disc without text Silicone-free: No	244643

Small rotary actuator, not lockable

		Art. No.
	Ø 39 mm Black Designation plate: 0/OFF – I/ON Number of switching positions: 2 Lockable in: Not padlockable Switching function: Latching / Latching Silicone-free: Yes	244646
	Ø 39 mm Black Designation plate: 0/OFF – I/ON Number of switching positions: 2 Lockable in: Not padlockable Switching function: Latching / Latching Silicone-free: No	244647


Control Devices

Contact element For mounting rail mounting NC

With gold-plated contacts

8082/3-11-1-1 Art. No. 275527



	Ø 39 mm Black Designation plate: I – 0 – II Number of switching positions: 3 Lockable in: Not padlockable Switching function: Latching / Latching / Latching Silicone-free: Yes	244648
	Ø 39 mm Black Designation plate: I – 0 – II Number of switching positions: 3 Lockable in: Not padlockable Switching function: Latching / Latching / Latching Silicone-free: No	244649


Small rotary actuator, lockable BG727

Art. No.

	Ø 39 mm Black Designation plate: 0/OFF – I/ON Number of switching positions: 2 Lockable in: One pos. with one lock Switching function: Latching / Latching Silicone-free: Yes	244650
	Ø 39 mm Black Designation plate: 0/OFF – I/ON Number of switching positions: 2 Lockable in: One pos. with one lock Switching function: Latching / Latching Silicone-free: No	244651
	Ø 39 mm Black Designation plate: I – 0 – II Number of switching positions: 3 Lockable in: One pos. with one lock Switching function: Latching / Latching / Latching Silicone-free: Yes	244652
	Ø 39 mm Black Designation plate: I – 0 – II Number of switching positions: 3 Lockable in: One pos. with one lock Switching function: Latching / Latching / Latching Silicone-free: No	244653

Illuminated pushbutton (spring return) BG735

Art. No.

	Ø 39 mm Black All colours Silicone-free: Yes	244654
	Ø 39 mm Black All colours Silicone-free: No	244655

Control Devices

Contact element For mounting rail mounting NC

With gold-plated contacts

8082/3-11-1-1 Art. No. 275527



Spare Parts

Mushroom stay-put button with key

		Art. No.
	Ø 39 mm Red/black Closing: MS2 Silicone-free: Yes	270409
	Ø 39 mm Red/black Closing: MS2 Silicone-free: No	270412
	Ø 39 mm Red/black Closing: MS3 Silicone-free: Yes	270410
	Ø 39 mm Red/black Closing: MS3 Silicone-free: No	270413
	Ø 39 mm Red/black Closing: MS4 Silicone-free: Yes	270411
	Ø 39 mm Red/black Closing: MS4 Silicone-free: No	270414

Control Devices

Contact element For mounting rail mounting NC

With gold-plated contacts

8082/3-11-1-1 Art. No. 275527



Key-operated switch actuator

BG008		Art. No.
	Ø 39 mm Black Closing: MS1 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: Yes	244573
	Ø 39 mm Black Closing: MS2 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: Yes	272935
	Ø 39 mm Black Closing: MS2 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: No	270418
	Ø 39 mm Black Closing: MS3 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: Yes	274089
	Ø 39 mm Black Closing: MS3 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: No	270419
	Ø 39 mm Black Closing: MS4 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: Yes	272936
	Ø 39 mm Black Closing: MS4 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: No	270420


Control Devices

Contact element For mounting rail mounting NC

With gold-plated contacts

8082/3-11-1-1 Art. No. 275527



	Ø 39 mm Black Closing: MS1 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: Yes	244632
	Ø 39 mm Black Closing: MS2 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: Yes	274090
	Ø 39 mm Black Closing: MS2 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: No	270421
	Ø 39 mm Black Closing: MS3 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: Yes	274091
	Ø 39 mm Black Closing: MS3 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: No	270422
	Ø 39 mm Black Closing: MS4 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: Yes	274092
	Ø 39 mm Black Closing: MS4 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: No	270423

Control Devices


Contact element For mounting rail mounting NC

With gold-plated contacts

8082/3-11-1-1 Art. No. 275527



Mushroom stay-put button with EM-STOP key

BG009		Art. No.
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS2 Silicone-free: Yes	274099
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS2 Silicone-free: No	270415
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS3 Silicone-free: Yes	274100
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS3 Silicone-free: No	270416
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS4 Silicone-free: Yes	274101
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS4 Silicone-free: No	270417

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.