

Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528

STAHL



- Large selection of different actuators
- Versions as an NC with positive opening, NO or disconnect terminal

MY R. STAHL 8082E



R. STAHL Series 8082 contact elements have an NO contact and a positive opening operation NC contact, made from silver-nickel or gold-plated. They can be easily combined with contact blocks and enable customised installations, also due to the large selection of the various actuators. They are connected via screw or spring clamp terminals.

Technical Data

Explosion Protection

Scope of validity	European Union (ATEX) CEC IECEX NEC
Application range (Zones)	1 2
IECEX gas certificate	IECEX PTB 17.0037U
IECEX gas explosion protection	Ex db eb IIC T6 / T5 Gb
IECEX firedamp certificate	IECEX PTB 17.0037U
IECEX firedamp protection	Ex db eb I Mb
ATEX gas certificate	PTB 17 ATEX 1012 U
ATEX gas explosion protection	⊕ II 2 G Ex db eb IIC T6 / T5 Gb
ATEX firedamp certificate	PTB 17 ATEX 1012 U
ATEX firedamp protection	⊕ I M2 Ex db eb I Mb
UL gas certificate	E182378V1S9
Marking cULus	Class I, Div. 2, Groups A,B,C,D; Class I, Zone 1, AEx/Ex db eb IIC
Certificates	Brazil (ULB), Canada (UL), China (CQST), IECEX (PTB), Korea (KTL), USA (UL)
Notes	Product label may vary. Series devices are labelled with ATEX, IECEX, NEC and CEC.

Electrical Data

Max. rated operational voltage	550 V
Min. rated operational voltage	24 V
Rated operational current	10 mA / 150 A
Rated operational current note	- Gold-plated contacts: 10 to 150 mA switching current - Silver-nickel contacts from 150 mA switching current. - For corrosive environments and offshore applications, we recommend the use of 8082 snap action switches.
Electrical service life	10 ⁹ operating cycles

Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528



Electrical Data

Mechanical service life	10 ⁶ operating cycles
-------------------------	----------------------------------

Ambient Conditions

Ambient temperature °C	-60 °C ... +70 °C (T6) -60 °C ... +85 °C (T5)
------------------------	--

Ambient temperature °F	-76 °F ... +158 °F (T6) -76 °F ... +185 °F (T5)
------------------------	--

Ambient temperature °F	-60 °C ... +75 °C (T6) -60 °C ... +90 °C (T5)
------------------------	--

Ambient temperature °F	-76°F ... +167°F (T6) -76°F ... +194°F (T5)
------------------------	--

Operating temperature	-60 °C ... +100 °C
-----------------------	--------------------

Operating temperature	-76 °F ... +212 °F
-----------------------	--------------------

Operating temperature NEC	-60 °C ... +95 °C
---------------------------	-------------------

Operating temperature NEC	-76 °F ... +203 °F
---------------------------	--------------------

Mechanical Data

Degree of protection (IP) (IEC 60529)	IP20
---------------------------------------	------

Enclosure material	Polyamide
--------------------	-----------

Contact material	Gold-plated
------------------	-------------

Silicone-free	Yes
---------------	-----

Solid connection cross section	0.32 – 2.5 mm ²
--------------------------------	----------------------------

Connection cross-section AWG single stranded	22 AWG to 14 AWG
--	------------------

Finely stranded connection cross section	0.32 – 2.5 mm ²
--	----------------------------

Finely stranded connection cross-section AWG	22 AWG to 14 AWG
--	------------------

Connection cross-section, finely stranded with core end sleeve	0.32 – 2.5 mm ²
--	----------------------------

Connection cross-section, finely stranded with core end sleeve AWG	AWG22 - AWG14
--	---------------

Number of NOs	1
---------------	---

Packaging unit	1
----------------	---

Weight	25 g
--------	------

Weight	0.055 lbs
--------	-----------

Mounting / Installation

Tightening torque	1.2 Nm
-------------------	--------

Tightening torque lbf in	10.62 lbf in
--------------------------	--------------

Connection type	Screw terminal
-----------------	----------------

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations

Accessories

Pushbutton

BG001

Art. No.

Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528



	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: Yes	223691
	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: No	223692
Mushroom pushbutton, black BG003		Art. No.
	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: Yes	244563
	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: No	244564
Mushroom pushbutton, red BG004		Art. No.
	Ø 39 mm Red/black Designation plate: Red, blank disc without text Silicone-free: Yes	244565
	Ø 39 mm Red/black Designation plate: Red, blank disc without text Silicone-free: No	244566
Mushroom stay-put button with key BG006		Art. No.
	Ø 39 mm Red/black Closing: MS1 Silicone-free: Yes	223695
Mushroom stay-put button with key BG006		Art. No.
	Ø 39 mm Red/black Closing: MS1 Silicone-free: No	223696
Key-operated switch actuator BG008		Art. No.
	Ø 39 mm Black Closing: MS1 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: No	244574

Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528



	<p>Ø 39 mm Black Closing: MS1 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: No</p>	244633
--	---	--------

Mushroom stay-put button with EM-STOP key

BG009 **Art. No.**

	<p>Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS1 Silicone-free: Yes</p>	223693
	<p>Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS1 Silicone-free: No</p>	223694

Mushroom stay-put button EM-STOP

BG010 **Art. No.**

	<p>Ø 39 mm Yellow/red Designation plate: With yellow backing plate Silicone-free: Yes</p>	223697
	<p>Ø 39 mm Yellow/red Designation plate: With yellow backing plate Silicone-free: No</p>	223698

Mushroom stay-put button, black

BG012 **Art. No.**

	<p>Ø 39 mm Black Silicone-free: Yes</p>	223699
	<p>Ø 39 mm Black Silicone-free: No</p>	223700

Mushroom pushbutton 55 mm red

BG014 **Art. No.**

	<p>Ø 55 mm Black/red Designation plate: Red, blank disc without text Silicone-free: Yes</p>	244634
--	---	--------

Mushroom pushbutton 55 mm red

BG014 **Art. No.**

	<p>Ø 55 mm Black/red Designation plate: Red, blank disc without text Silicone-free: No</p>	244635
--	--	--------

Control Devices


Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528




Mushroom stay-put button 55 mm EM-STOP

		Art. No.
BG015 	Ø 55 mm Yellow/red Designation plate: With yellow backing plate Silicone-free: Yes	244636


Mushroom maintained 55 mm E-STOP

		Art. No.
BG015 	Ø 55 mm Yellow/red Designation plate: With yellow backing plate Silicone-free: No	244637


Twin pushbutton

		Art. No.
BG023 	Black Silicone-free: Yes	244638
	Black Silicone-free: No	244639

Mushroom pushbutton 55 mm black

		Art. No.
BG703 	Ø 55 mm Black Designation plate: Black, blank disc without text Silicone-free: Yes	244642
	Ø 55 mm Black Designation plate: Black, blank disc without text Silicone-free: No	244643

Small rotary actuator, not lockable

		Art. No.
BG726 	Ø 39 mm Black Designation plate: 0/OFF – I/ON Number of switching positions: 2 Lockable in: Not padlockable Switching function: Latching / Latching Silicone-free: Yes	244646
	Ø 39 mm Black Designation plate: 0/OFF – I/ON Number of switching positions: 2 Lockable in: Not padlockable Switching function: Latching / Latching Silicone-free: No	244647


Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528



	Ø 39 mm Black Designation plate: I – 0 – II Number of switching positions: 3 Lockable in: Not padlockable Switching function: Latching / Latching / Latching Silicone-free: Yes	244648
	Ø 39 mm Black Designation plate: I – 0 – II Number of switching positions: 3 Lockable in: Not padlockable Switching function: Latching / Latching / Latching Silicone-free: No	244649


Small rotary actuator, lockable BG727

Art. No.

	Ø 39 mm Black Designation plate: 0/OFF – I/ON Number of switching positions: 2 Lockable in: One pos. with one lock Switching function: Latching / Latching Silicone-free: Yes	244650
	Ø 39 mm Black Designation plate: 0/OFF – I/ON Number of switching positions: 2 Lockable in: One pos. with one lock Switching function: Latching / Latching Silicone-free: No	244651
	Ø 39 mm Black Designation plate: I – 0 – II Number of switching positions: 3 Lockable in: One pos. with one lock Switching function: Latching / Latching / Latching Silicone-free: Yes	244652
	Ø 39 mm Black Designation plate: I – 0 – II Number of switching positions: 3 Lockable in: One pos. with one lock Switching function: Latching / Latching / Latching Silicone-free: No	244653

Illuminated pushbutton (spring return) BG735

Art. No.

	Ø 39 mm Black All colours Silicone-free: Yes	244654
	Ø 39 mm Black All colours Silicone-free: No	244655

Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528



Spare Parts

Mushroom stay-put button with key

		Art. No.
	Ø 39 mm Red/black Closing: MS2 Silicone-free: Yes	270409
	Ø 39 mm Red/black Closing: MS2 Silicone-free: No	270412
	Ø 39 mm Red/black Closing: MS3 Silicone-free: Yes	270410
	Ø 39 mm Red/black Closing: MS3 Silicone-free: No	270413
	Ø 39 mm Red/black Closing: MS4 Silicone-free: Yes	270411
	Ø 39 mm Red/black Closing: MS4 Silicone-free: No	270414

Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts


8082/3-11-2-1 Art. No. 275528



Key-operated switch actuator

BG008

Art. No.

		Art. No.
	Ø 39 mm Black Closing: MS1 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: Yes	244573
	Ø 39 mm Black Closing: MS2 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: Yes	272935
	Ø 39 mm Black Closing: MS2 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: No	270418
	Ø 39 mm Black Closing: MS3 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: Yes	274089
	Ø 39 mm Black Closing: MS3 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: No	270419
	Ø 39 mm Black Closing: MS4 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: Yes	272936
	Ø 39 mm Black Closing: MS4 Number of switching positions: 2 Switching function: Latching / Latching Silicone-free: No	270420


Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528



	Ø 39 mm Black Closing: MS1 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: Yes	244632
	Ø 39 mm Black Closing: MS2 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: Yes	274090
	Ø 39 mm Black Closing: MS2 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: No	270421
	Ø 39 mm Black Closing: MS3 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: Yes	274091
	Ø 39 mm Black Closing: MS3 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: No	270422
	Ø 39 mm Black Closing: MS4 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: Yes	274092
	Ø 39 mm Black Closing: MS4 Number of switching positions: 3 Switching function: Latching / Latching / Latching Silicone-free: No	270423

Control Devices

Contact element For mounting rail mounting NO

With gold-plated contacts

8082/3-11-2-1 Art. No. 275528



Mushroom stay-put button with EM-STOP key

BG009		Art. No.
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS2 Silicone-free: Yes	274099
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS2 Silicone-free: No	270415
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS3 Silicone-free: Yes	274100
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS3 Silicone-free: No	270416
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS4 Silicone-free: Yes	274101
	Ø 39 mm Yellow/red Designation plate: With yellow backing plate Closing: MS4 Silicone-free: No	270417

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.