

IS530.M1Smart Phone Set miningEEA Art. No. 307070




- Explosion-protected phone for mining industry with push-to-talk option
- SOS key for lone-worker protection
- NFC access control
- Universal powerful replaceable battery for multi-shift operation
- Android Enterprise Recommended
- Zero touch capable
- Managed via MDM system

MY R. STAHL MPHONEA



Thanks to its freely programmable key, optionally with PTT, the professional mobile phone can be used like a radio device. Its ISM interface for the connection of other accessories such as RSM or PTT headsets make it suitable for MCPTT communication. The Android Enterprise Recommended device is zero touch capable and can be easily managed via an MDM system. The powerful battery and the charging options via desktop or multi-charger complete the highlights of this ultra-robust mobile device with a comfortable feel.

Technical Data

General	
Technology	Telephone
Version	Smartphone
Explosion Protection	
Application range	Mining M1, M2
Application range (firedamp protection)	M1 M2
Scope	Mining: EU (CE / ATEX) Mining: Global (IECEX)
IECEX certification	EPS 19.0062X
ATEX certification	EPS 19 ATEX 1 126 X
IECEX Firedamp protection	Ex ia I Ma IP64
ATEX Firedamp protection	 I M1 Ex ia I Ma IP64
Electrical Data	
Processor type	Qualcomm SDM660 Octa-core
Processor details	Kryo Gold-Quad core 2.2 GHz; Kryo Silver-Quad core 1.8 GHz
Main memory	4 GB
Data memory	64 GB int. + SD up to 128 GB
Operating system	Android 10 (upgr. 13)
Mobile standard	2G, 3G, 4G
Interface medium	WiFi 802.11 a/b/g/n/ac/e/k/r/h
Frequency range	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39
Optional interface 1	Bluetooth 5

IS530.M1Smart Phone Set miningEEA Art. No. 307070

Electrical Data

Optional interface 2	13 MP AF camera (rear)
Addition 3/Option box	5 MP front camera
SD card type/size	MicroSD/up to 128 GB
SIM card number	Double SIM
SIM card size	Micro
Battery	3600 mAh
Connections	GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication Hotspot for max. 8 connections

Display

Display version 2	Gorilla glass® 3. generation
Display size in inches	4.50
Display size in cm	11.43
Display resolution	FWVGA
Touch screen	Capacitive
Touchscreen material	Gorilla glass corning 3rd gen.
Backlight	LED technology

Ambient Conditions

Ambient temperature	-20 – 60
Ambient temperature	-20 °C ... +60 °C

Mechanical Data

Degree of protection (IP)	IP68
Further protection	Water- and dustproof MIL-STD-810H
MIL-standard	810G (h/l temp., shock, vibr.)
Width	80 mm
Height	155 mm
Depth	25 mm
Weight	325 g
Weight	0.72 lb

Components

More specifications	SOS key for loneworker protection, LWP ready (requires third-party application, based on country-specific regulations) Universal, 13-pin ISM (multifunction) interface for connecting additional devices for a wide range of applications Dual micro-SIM Amplified loudspeaker Accelerometer, gyroscope, light, magnetic, proximity and pressure sensor magnetic charging connector
---------------------	--

Included in delivery

- > Smartphone with integrated battery
- > Universal power adapter
- > i.safe PROTECTOR 2.0
- > i.safe PROTECTOR 3.0
- > Screwdriver
- > Screen protector
- > Safety regulations
- > Quick Start Guide

IS530.M1Smart Phone Set miningEEA Art. No. 307070

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.