

IS-TC1A.2 Thermal Camera Set Art. No. 317720



- Ideal for Mobile Worker Applications
- capture, analyse and document thermal images
- direct data transfer via ISM interface
- direct interface connection with device, no Bluetooth® required
- power supplied via connected device, thus no battery required

**MY R. STAHL MPERIPHER-
ALSA**



The explosion-protected IS-TC1A.1 thermal camera, in combination with the IS530.1 industrial smartphone detects temperatures in hazardous areas from -40 °C to 330 °C in a matter of seconds via the Seek Thermal app (free download in Google Play Store). The thermal images and videos are processed and documented directly via the ISM interface of the IS530.1 smartphone.

Technical Data

Explosion Protection

Application range (Zones)	2 22
Application range (divisions)	Class I, Division 2 Class II, Division 2 Class III, Division 2
Scope	EU (CE / ATEX) Global (IECEx) USA (NEC) Canada (CEC)
IECEx certification	EPS 21.0064X
ATEX certification	EPS 21 ATEX 1 207 X
NEC certification	70220252
CEC certification	70220252
IECEx gas explosion protection	Ex ic IIC T4 Gc
IECEx dust explosion protection	Ex ic IIIC T135°C Dc
ATEX gas explosion protection	⊕ II 3G Ex ic IIC T4 Gc
ATEX dust explosion protection	⊕ II 3D Ex ic IIIC T135°C Dc
NEC gas explosion protection	Class I, Div 2, Groups A, B, C, D, T4
NEC dust explosion protection	Class II, Div 2, Groups F, G , T135°C Class III, Div 2
CEC gas explosion protection	Class I, Div 2, Groups A, B, C, D, T4
CEC dust explosion protection	Class II, Div 2, Groups F, G , T135°C Class III, Div 2

Electrical Data

Frequency	<9 Hz - 32 Hz
Interfaces	ISM-socket

Camera Data

Viewing angle	35° H, 27° V
---------------	--------------

IS-TC1A.2 Thermal Camera Set Art. No. 317720

Camera Data

Total pixels	200 (H) x 150 (V)
Pixel	30000 pixel

Ambient Conditions

Ambient temperature	-10 – 60
---------------------	----------

Mechanical Data

Version	Fixed viewing angle
Degree of protection (IP)	IP68
Weight	1 kg
Weight	2.2 lb

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.